

DECLARATION OF PERFORMANCE

DOP – BDLMH25



- | | |
|--|---|
| 1. Identification Code: | BDLMH25: Bond It LMH25 Low Mod Hybrid Sealant & Adhesive |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Exterior & Interior Use. 25LM CC Sealant. |
| 4. Manufacturer: | Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | 3 plus 3 |
| 7. Notified Body: | 1023 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

IMPORTANT CHARACTERISTIC	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Fire behaviour	Class E	EN 15651-1: 2012 - 12
Release of hazardous chemicals to health and/or the environment	Evaluated	
Water and Air Tightness		
a) Stability under load	≤3mm	
b) Volume loss	≤5%	
c) Tensile behaviour, i.e. stress expansion and pre-tension after immersion in water	Passed (NF)	
d) Tensile properties / secant modulus in cold climate (-30°C)	≤ 0.6 MPa	
e) Tensile properties and pre-tensioning in a cold climate (-30°C)	Passed (NF)	
Durability	Passed (NF)	

10. The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9. Please see the technical datasheets, safety data sheets and our technical documentation.

This declaration of performance is issued under the responsibility of the manufacturer.

A Oxley

Amy Oxley
Regulatory & Technical Data Manager

Issue 1: 8th November 2021

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com

DECLARATION OF PERFORMANCE

DOP – BDLMH25



- | | |
|--|---|
| 1. Identification Code: | BDLMH25: Bond It LMH25 Low Mod Hybrid Sealant & Adhesive |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Exterior & Interior Use. 25LM CC Sealant. |
| 4. Manufacturer: | Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | 3 plus 3 |
| 7. Notified Body: | 1023 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

IMPORTANT CHARACTERISTIC	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Fire behaviour	Class E	EN 15651-1: 2012 - 12
Release of hazardous chemicals to health and/or the environment	Evaluated	
Water and Air Tightness		
a) Stability under load	≤3mm	
b) Volume loss	≤5%	
c) Tensile behaviour, i.e. stress expansion and pre-tension after immersion in water	Passed (NF)	
d) Tensile properties / secant modulus in cold climate (-30°C)	≤ 0.6 MPa	
e) Tensile properties and pre-tensioning in a cold climate (-30°C)	Passed (NF)	
Durability	Passed (NF)	

10. The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9. Please see the technical datasheets, safety data sheets and our technical documentation.

This declaration of performance is issued under the responsibility of the manufacturer.

A Oxley

Amy Oxley
Regulatory & Technical Data Manager

Issue 1: 20th October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com