

Construction Products Regulations (EU) 305 2011

## **DECLARATION OF PERFORMANCE**

DOP - BDM (WH/GR/BL/T/BR)



1 Identification Code:

2. Batch Identification:

By batch number – see print on packaging

3. Intended uses:

FEXT-INT Façade Sealant for Exterior and Interior Use 12.5E. S1 Sanitary sealant

4. Manufacturer:

Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business Park Elland West Yorkshire HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of

constancy:

System 3

7. Notified Body: NB01213 & 0074

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightne	BS EN 15651-1,3:2012	
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤30%	Tested on aluminium with
Tensile properties after water	NF	primer, glass without primer
immersion		
Durability	Pass	
Microbiological Growth	S1	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Kayleigh Cox-Nowak Technical Manager

Elland

**Issue 2:** 3<sup>rd</sup> May 2019

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com



Construction Products Regulations (EU) 305 2011

## **DECLARATION OF PERFORMANCE**

DOP - BDM (WH/GR/BL/T/BR)



1 Identification Code:	Bond It Multi-Mate Multi-Purpose Silicone
2. Batch Identification:	By batch number – see print on packaging
3. Intended uses:	<b>F EXT-INT</b> Façade Sealant for Exterior and Interior Use 12.5E. <b>S1</b> Sanitary sealant
4. Manufacturer:	Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business Park Elland West Yorkshire HX5 9DN
5. Authorised Representative:	Not applicable
6. System of assessment and Verification of constancy:	System 3

NB01213 & 0074

Not Applicable

q	Dec	lared	performance:
J.		ıaıcu	Dellolliance.

8. European Technical Assessment:

7. Notified Body:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD	
Reaction to Fire	Class E		
Release of Chemicals	None	See MSDS	
Water Tightness and Air Tightne	BS EN 15651-1,3:2012		
Resistance to Flow	≤3mm	Conditioning method A	
Loss of Volume	≤30%	Tested on aluminium with	
Tensile properties after water	NF	primer, glass without primer	
immersion			
Durability	Pass		
Microbiological Growth	S1		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Kayleigh Cox-Nowak Technical Manager

Elland

Issue 1: 20<sup>th</sup> October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com