

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE DOP – BDSPRO WH/MGR



1 Identification Code: BDSPRO: Bond It Seal Pro Sanitary Sealant &

Adhesive

2. Batch Identification: By batch number – see print on packaging

3. Intended uses: F EXT-INT Façade Sealant for Exterior &

Interior Use. 25LM CC Sealant. XS1 for

Sanitary Use.

4. Manufacturer: Seal It Services Ltd t/a Bond It

Unit G16 River Bank Way Lowfields Business Park

Elland

West Yorkshire

HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of 3 plus 3

constancy:

7. Notified Body: 1023

8. European Technical Assessment: Not Applicable

9. Declared performance:

IMPORTANT CHARACTERISTIC	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Fire behaviour	Class E	
Release of hazardous chemicals to	Evaluated	
health and/or the environment		
Water and Air Tightness		
a) Stability under load	≤3mm	
b) Volume loss	≤5%	
c) Tensile behaviour, i.e.	Passed (NF)	FN 45654 4 2042 42
stress expansion and pre-		EN 15651-1: 2012 - 12
tension after immersion in		
water		
d) Tensile properties / secant	≤ 0.6 MPa	
modulus in cold climate (-		
30°C)		
e) Tensile properties and	Passed (NF)	
pre-tensioning in a cold		
climate (-30°C)		
Durability	Passed (NF)	
Microbial Resistance	XS1	DIN EN ISO 846 (11/2020)

^{10.} The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9. Please see the technical datasheets, safety data sheets and our technical documentation.

This declaration of performance is issued under the responsibility of the manufacturer.



Amy Oxley Regulatory & Technical Data Manager

Issue 1: 14th February 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com



Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE DOP – BDSPRO WH/MGR



1 Identification Code: BDSPRO: Bond It Seal Pro Sanitary Sealant &

Adhesive

2. Batch Identification: By batch number – see print on packaging

3. Intended uses: F EXT-INT Façade Sealant for Exterior &

Interior Use. 25LM CC Sealant. XS1 for

Sanitary Use.

4. Manufacturer: Seal It Services Ltd t/a Bond It

Unit G16 River Bank Way Lowfields Business Park

Elland

West Yorkshire

HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of 3 plus 3

constancy:

7. Notified Body: 1023

8. European Technical Assessment: Not Applicable

9. Declared performance:

3. Declared performance.			
IMPORTANT CHARACTERISTIC	PERFORMANCE	HARMONISED TECHNICAL	
		SPECIFICATION	
Fire behaviour	Class E		
Release of hazardous chemicals to	Evaluated		
health and/or the environment			
Water and Air Tightness			
a) Stability under load	≤3mm		
b) Volume loss	≤5%		
c) Tensile behaviour, i.e.	Passed (NF)		
stress expansion and pre-		EN 15651-1: 2012 - 12	
tension after immersion in			
water			
d) Tensile properties / secant	≤ 0.6 MPa		
modulus in cold climate (-			
30°C)			
e) Tensile properties and	Passed (NF)		
pre-tensioning in a cold			
climate (-30°C)			
Durability	Passed (NF)		
Microbial Resistance	XS1	DIN EN ISO 846 (11/2020)	

^{10.} The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9. Please see the technical datasheets, safety data sheets and our technical documentation.

This declaration of performance is issued under the responsibility of the manufacturer.

Amy Oxley

Aoxley

Regulatory & Technical Data Manager

Issue 1: 30th October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com