


DECLARATION OF PERFORMANCE**DOP - BDLN7**

- 1 Identification Code: **BDLN7: Bond It LN7 LMA Silicone**
2. Batch Identification: **By batch number – see print on packaging**
3. Intended uses: **F EXT-INT Façade Sealant for Exterior and Interior Use. G CC 25LM Glazing Silicone**
4. Manufacturer: **Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN**
5. Authorised Representative: **Not applicable**
6. System of assessment and Verification of constancy: **System 3**
7. Notified Body: **0074**
8. European Technical Assessment: **Not Applicable**
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤10%	Tested on aluminium without primer, glass without primer
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Dean Morgan
Managing Director
Elland

Issue 2: 2nd November 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com



Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

DOP - BDLN7



- 1 Identification Code: **BDLN7: Bond It LN7 LMA Silicone**
2. Batch Identification: **By batch number – see print on packaging**
3. Intended uses: **F EXT-INT Façade Sealant for Exterior and Interior Use. G CC 25LM Glazing Silicone**
4. Manufacturer: **Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN**
5. Authorised Representative: **Not applicable**
6. System of assessment and Verification of constancy: **System 3**
7. Notified Body: **2538**
8. European Technical Assessment: **Not Applicable**
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤10%	Tested on aluminium without primer, glass without primer
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Dean Morgan

Dean Morgan
Managing Director
Elland

Issue 2: 2nd November 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com