

DECLARATION OF PERFORMANCE


DOP – GRIPBOND PRO (Code: BDMSP CL/WH/BL/GR)

- 1 Identification Code: Bond It **GRIPBOND PRO** Adhesive and Sealant
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F-INT** Façade sealant for Internal use
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 4
7. Notified Body:
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012 Conditioning method A Tested on aluminium without primer
Resistance to Flow	< 3mm	
Loss of Volume	<45%	
Tensile properties after water immersion	>25%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
Issue 2: 17 Nov 2017