

DECLARATION OF PERFORMANCE**DOP – BDNCCWH**

- 1 Identification Code: **BDNCCWH:** Bond It No Crack Caulk Sealant
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use. Class **12.5P**.
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 2538
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	NPD	
Tensile properties after water immersion	NPD	
Durability	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Simon Hodgson
Technical Manager, Bond It
Elland.
Issue 1 - 21st September 2020

Seal It Services Ltd/ T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com

DECLARATION OF PERFORMANCE

DOP – BDNCCWH



- 1 Identification Code: **BDNCCWH: Bond It No Crack Caulk Sealant**
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use. Class **12.5P**.
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 2538
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012 Conditioning method A
Resistance to Flow	≤3mm	
Loss of Volume	NPD	
Tensile properties after water immersion	NPD	
Durability	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Simon Hodgson
Technical Manager, Bond It
Elland.
Issue 1 – 20th October 2022

Seal It Services Ltd/ T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com