

DECLARATION OF PERFORMANCE

DOP – WP100

- | | |
|--|---|
| 1. Identification Code: | Bond It WP100 Oxime Silicone |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Exterior and Interior Use. G Glazing Sealant. XS2 . |
| 4. Manufacturer: | Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business Park Elland West Yorkshire, HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651 1:2012
Resistance to Flow	≤3mm	Conditioning method B. Tested on Mortar M1 without primer.
Loss of Volume	≤20%	
Tensile properties at maintained extension	Pass	EN15651-3:2012 Conditioning method B. Tested on Aluminium without primer.
Tensile Properties – secant modulus	Pass	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Adhesion/cohesion after exposure to heat, water and artificial light	Pass	
Elastic Recovery	>40%	
Durability	Pass	
Microbiological growth	2	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Amy Oxley
Regulatory & Technical Data Manager

Issue 5: 16th March 2022