PRODUCT SELL SHEET



## **CONTACT ADHESIVE SF**

**SOLVENT-FREE FORMULATION** 



## PART OF THE GLUES & ADHESIVE RANGE

A heavy duty, waterbased, spreadable contact adhesive.

**Uses**: For securing floorcoverings accessories and profiles to internal vertical and horizontal surfaces such as, walls, ceilings and stairs. Sticks vinyl, linoleum, textiles, rubber floorcoverings, EPDM, flexible stair nosings, vinyl and rubber skirtings, laminate, wood, metal, plastic, plaster, painted surfaces, cork, leather and expanded polystyrene. For use in general building installations, shopfitting, laminating, furniture manufacture, roofing applications and DIY. Can be used externally if protected frrom rain and water.

## **Benefits:**

- Solvent-free formulation.
- Supplied in recycled plastic tubs.
- Easy to use.
- Non-flammable.
- Can be used on porous and non-porous materials.
- Extended working time.
- Excellent bond strength.
- Internal and external use (if protected from water).
- Safer to use than traditional solvented contact adhesives.
- Water clean up.
- Coverage

Depending upon substrate condition and porosity the approximate coverage rates will be approximately 10m² per litre.

Code	Colour	Вох	Size	Barcode
BDCASF5	White	1	5L	5056437401526

## Open Time @ 20°C Approx. 30 mins Full Cure @ 20°C /50% RH ca. 48 hours post application Density ca. 1.1g/cm³ Application Temperature Limits +5 to +30°C Viscosity ca. 17,000Cps at 20°C Temperature Resistance -30 to +100°C











