



Never compromise on quality!



SEAMING TAPE

Seaming Tape for Artificial/ Synthetic Grass



PRO (HYBRID) RANGE OF SEALANTS & ADHESIVES

Description:

A laminated geotextile seaming tape for jointing Artificial grass carpets. Strong, rot resistant, impervious to moisture.

Bond It **SEAMING TAPE** consists of 2 plies of non-woven fabric bonded together with a strong adhesive. The back layer has a smooth impervious surface whilst the top face has a more open structure to aid bonding to our ASTRO PRO Hybrid Adhesive.



Uses

SEAMING TAPE is designed for use in conjunction with Bond It ASTRO PRO ADHESIVE and is suitable for use with all tufted or needlepunch artificial grass carpets.

Application

Fold back the artificial turf 30-40cm on each side along the length of the join. Unroll joint tape shiny side down along the entire length of the join. Apply an even layer of adhesive to the tape either direct from the cartridge using the notched nozzle supplied, or use a suitable sized notched applicator to spread the adhesive. Press the edges of the carpet into the adhesive and apply pressure all along the seam to ensure that the tape and the grass are firmly bonded. Allow a minimum of 24 hours for the adhesive to cure.

Size

Roll size is 200mm x 100 metres.

Colour

White.

Shelf Life

Indefinite.

Storage Conditions

Keep dry and store at a temperature between 0 and 30°C.

Disposal of Containers

Do not leave empty packaging on site where bags could be harmful to children, animals or the environment. Remove any discarded packaging to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Low hazard product. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Colour	White
Material	Non woven geotextile
Weight	180gsm
Storage Temperature	0-30°C
Temperature Stability	-25°C to +100°C

Product Details:

Code:	BDAST200
Size:	200mm x 100 metres
Colour:	White
Barcode:	5056437400581



Part of the Bond It Pro Hybrid Sealants & Adhesive Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V2 24/07/20
 Supersedes: V1 15/01/17