

bond it

Never compromise on quality!



CLEAR COAT BLOCK SEALER

Sealer for Protecting Block Paving Driveways and Paths



DRIVE ALIVE RANGE

Description:

A ready-to-use, clear sealant for block paving, paths and driveways.

Benefits:

- ◆ *Protects from water penetration; staining and dirt/grime build-up.*
- ◆ *Advanced "Hybrid" technology.*
- ◆ *Ready to use.*
- ◆ *Excellent abrasion and chemical resistance.*
- ◆ *Contains fungicide which inhibits organic growth.*
- ◆ *Solvent-free - low odour.*
- ◆ *Facilitates easy cleaning.*
- ◆ *Improves water and UV resistance.*

Uses

Designed to protect from water penetration, oil or grease spillages and dirt/grime build-up. Will enhance present colour and extend the lifespan of the treated surface. Designed for use with cobble lock block paving only.

Preparation

Remove any moss or lichen that may be present. For best results use DRIVE ALIVE ORGANIC CLEANER prior to application (ensure the residue is thoroughly washed off and left to dry for 48 hours prior to application). Ensure the surface to be treated is free from oil, grease, dust and any other loose material that may hinder adhesion. It is recommended that a test be carried out on a small inconspicuous area to ensure the required effect is achieved.



Application

DRIVE ALIVE CLEAR COAT BLOCK SEALER is ready to use, and does not require diluting. We advise that you test this product on a small inconspicuous area prior to use to check compatibility. STIR WELL BEFORE USE. Ensure that the surface is completely dry. Apply a single coat using either a brush, roller or squeegee, ensuring no pooling or ponding occurs. Allow 3-4 hours drying time before trafficking the area. Application temperature between 5°C and 30°C. Colder humid conditions will slow drying times.

Drying Time

Approx 24 hours to attain full cure. Can take light foot traffic after

4 hours. Joints will take longer to dry. Note: Drying times will vary dependant on weather conditions, temperature and humidity. If applying to new paviers ensure that a sufficient period of weathering (check with manufacturer) has elapsed in order to avoid efflorescence occurring.

Note:

It is necessary to seal blocks prior to the application of any pointing or jointing compound. Some compounds have the capability of staining porous paving materials. Ensure **CLEAR COAT** has completely cured prior to pointing. Do not apply **CLEAR COAT** to any uncured wet pointing or to any dry mix cement compound. If applying **CLEAR COAT** to new paviers ensure a sufficient period of weathering (as recommended by the paving manufacturer) has elapsed in order to avoid efflorescence. Blocks can be resealed using a single coat of **CLEAR COAT** at 3 to 4 year intervals. The surface may still be sealed even when the surface tension appears to have reduced. Apply to a small test area and check a few days later. Avoid over application.

Limitations

Do not apply to wet or damp surfaces or in conditions of high humidity. Surfaces should be allowed to dry completely for 48 hours prior to application. Do not use if rain is imminent (protect from rain until dry). Do not apply to non-porous surfaces. Keep children and animals away and do not traffic until fully cured. Do not allow any run off to contaminate drains, waterways or plants. Do not use in temperatures below +5°C and above +30°C.

Coverage

One 4 Litre container will cover approximately 15m² for a single coat depending on surface porosity.

Container Size

4L rectangular plastic tub.

Colour

Milky white liquid.

Shelf Life

24 months from date of manufacture when stored in sealed tubs.

Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Physical Properties	Milky white liquid, non-flammable, zero VOC, water miscible
Application	STIR WELL BEFORE USE. Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	5°C to 30°C
Drying Time	1-2 hours in warm, sunny conditions
Coverage Rate	15m ² per 4 litre container
Cleaning	Rinse then wash brushes and rollers in warm, soapy water
Shelf Life	2 years



Product Details:

Code:	BDCCBS4
Colour:	Milky White
Size:	4L
Barcode:	5060021368300



Part of the Bond It Drive Alive Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT

Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 12/03/19
Supercedes: V3 11/06/12