

bond it

Never compromise on quality!



COLOUR ENHANCER

Coloured Concrete Solution to Revive Tired Driveways and Paths



DRIVE ALIVE RANGE

Description:

A ready-to-use, coloured solution for use on concrete, block paving and paving slabs.

Benefits:

- ◆ Restores colour.
- ◆ Protects from water penetration; staining and dirt/grime build-up.
- ◆ Advanced "Hybrid" technology.
- ◆ Ready to use.
- ◆ Excellent abrasion and chemical resistance.
- ◆ Contains fungicide which inhibits organic growth.
- ◆ Solvent-free - low odour.
- ◆ Facilitates easy cleaning.
- ◆ Improves water and UV resistance.

Uses

Designed to enhance coloured concrete and block paving, protect from water penetration, oil or grease spillages and dirt/grime build-up. Will enhance present colour and extend the lifespan of the treated surface.

Preparation

Remove any moss or lichen that may be present. For best results use BOND IT PATIO BLASTER prior to application (ensure the residue is thoroughly washed off and left to dry for 48 hours prior to application.) Ensure the surface to be treated is free from oil (DRIVE ALIVE OIL STAIN REMOVER should be used to remove any oil stains), grease, dust and any other loose material that may hinder adhesion. It is recommended that a test be carried out on a small inconspicuous area to ensure the required effect is achieved. Mask off all areas not to be coloured as product cannot be removed once applied. Wear gloves and overalls to protect clothes and skin from splashes. Place the container on polythene or cardboard prior to opening to contain any drips.



Application

DRIVE ALIVE COLOUR ENHANCER is ready to use, and does not require diluting. Stir well before use and periodically during application. A test on a small inconspicuous area is recommended to determine the depth of colour required. Apply using a brush or

roller. Do not over apply or allow puddling. This product will dry in 1 to 2 hours on a dry sunny day; however, cold or humid conditions will slow drying times. Do not traffic for 3-4 hours after application. Only to be used in conjunction with other BOND IT DRIVE ALIVE products. Wash hands and tools with soapy water after use. We recommend a single coat application but a maximum of two coats can be used on the first time of application. Paviers can be resealed using a single coat of **COLOUR ENHANCER**, if it is necessary. This can be determined by a small porosity test to the surface in an inconspicuous area. We suggest an area be subjected to a sprinkling of water via a watering can with rose attachment, if the water beads then a further application is not necessary as the seal is still intact. However, if the water is absorbed by the patio surface re-application can be performed. For patios with unknown treatments we would also suggest using the same test method to determine suitability. Adverse reactions can be caused if **COLOUR ENHANCER** is used over other existing sealers or treatments so should be avoided at all times. Avoid over application in all circumstances.

Limitations

PLEASE BATCH MATCH TO ENSURE CONSISTENT COLOUR.

As there may be differences in the colour between different production batches, always check that the batch numbers are the same. Do not apply to wet or damp surfaces or in conditions of high humidity. Surfaces should be allowed to dry completely for 48 hours prior to application. Do not use if rain is imminent (protect from rain until dry). Do not apply to non-porous surfaces. Keep children and animals away and do not traffic until fully cured. Do not allow any run off to contaminate drains, waterways or plants. Do not use in temperatures below +5°C and above +30°C.

Coverage

One 4 litre container will cover approximately 15m² depending on surface porosity for a single coat.

Container Size

4L rectangular plastic tubs.

Colour

Available in brindle, red, buff and charcoal.

Shelf Life

24 months from date of manufacture when stored in sealed tubs.

Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful

to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Physical Properties	Coloured liquid, non flammable, zero VOC, water miscible.
Application	STIR WELL BEFORE USE. Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	+5°C to +30°C
Drying Time	1-2 hours in warm, sunny conditions
Coverage Rate	approx. 15m ² per 4 litre container
Cleaning	Rinse then wash brushes and rollers in warm, soapy water
Shelf Life	2 years



Product Details:

Code:	BDCEGR4	BDCER4	BDCEBR4	BDCEBU4
Colour:	Charcoal	Red	Brindle	Buff
Size:	4L	4L	4L	4L
Barcode:	5060021367020	5060021367068	5060021367075	5060021367051



Part of the Bond It Drive Alive Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V9 14/6/22
Supersedes: V8 12/3/19