



STABILIZING SOLUTION

Water-Based Bonding and Priming Agent



BUILDERS COMPLETE RANGE

Description:

A clear, ready to use, water-based treatment for bonding and priming surfaces prior to painting and decorating. Suitable for interior and exterior use.

Uses

For use as a pre-treatment for surfaces which are old, weathered, chalky or porous. Suitable for use on most substrates including concrete, cement, plaster, plasterboard, renders, pebbledash and MDF, etc.

Preparation

Ensure all surfaces are clean and free from

any contaminants including loose and flaking material. Remove any mould or algae with MOULD-STOP, PATIO BLASTER or ORGANIC CLEANER prior to application.



Application

Do not dilute. Stir well and apply by brush, roller or airless spray. A second coat may be required on porous or powdery surfaces but allow 12 hours drying time between application of coats.

Limitations

Do not apply **STABILIZING SOLUTION** when the temperature is below 5°C or when rain or frost is imminent. However, this product can be applied to damp substrates.

Cleaning of Tools

Rinse equipment after use with plenty of clean water.

Coverage

6m² per litre, depending on porosity of substrate.

Container Size

5L plastic bottle.

Colour

White liquid.

Shelf Life

2 years from date of manufacture when stored in sealed bottles.

Storage Conditions

Store in cool, dry conditions in a sealed container between 5 & 30°C and protect from freezing and direct sunlight.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Appearance White liquid Flammability Non-flammable pH approximately 7-9 Solubility in Water Soluble

Product Details:

Colour:	White
Code:	BDH130
Size:	5L
Barcode:	5060021364777



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001; ISO 14001; ISO 45001

BOND IT

Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

