

Never compromise on quality!



SCRIM TAPE

Lightweight Drywall Joint Tape



TIGRIS TAPE RANGE

Description:

A trade grade, self-adhesive, fibreglass mesh tape which gives increased strength and extra reinforcement when joining plasterboard.

Benefits:

- Self-adhesive and repositionable.
- ◆ Joins dry wall, plaster walls & ceilings.
- Repairs cracks & patches holes.
- Quick & easy to apply.
- Flexible, will not bubble/blister.
- * Alkaline resistant will not rot.

Uses

For joint finishing, crack and hole repair. For drywall and plaster walls and ceilings.

Application

- **1.** Ensure surfaces are clean, free from dust and dry.
- **2.** Remove outer packaging from roll of tane
- **3.** Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
- 4. Cut with a knife or tear when finished.

Colour

White.

Size

2 inch x 90M.

Storage Conditions

Store in original, unopened packs in dry conditions, out of direct sunlight.

Shelf Life

12 months.


Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

This product will cause no major hazard or problem to the users health. Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.





Specification Summary

Backing	100% glass fibre
Adhesive	Acrylic latex
Total Weight	approx 65gsm
Thickness	0.2 mm

Weight(g/m2)	Fiberglass Yarn Tex		Tensile Strength(N/50mm)		Fabric Count(meshes/inch)			Latex(%)
Weight(g/m2)	Warp	Weft	Warp	Weft	Warp	Weft	Туре	Latex(%)
65±5g/m2	66	80	≥400	≥500	8±0.5	8±0.5	Leno weave	≥26

Product Details:

Colour:	White
Code:	BDSCRIM
Size:	2" x 90M
Barcode:	5056437400031



Part of the Bond It Tape Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or $new\ developments.\ The$ recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do

not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



6152 ISO 9001 ISO 14001; ISO 45001 **BOND IT**

Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V1 1/10/21 Supercedes: V