

SAVES NAILS

Multi-Purpose Rubber Based Grab Adhesive



GLUES & ADHESIVES RANGE

Description:

A multi-purpose, rubber based construction adhesive in mild solvents, that can replace mechanical fixings in a wide variety of domestic, commercial and industrial applications.

SAVES NAILS is a fast bonding adhesive with gap-filling properties to bridge gaps up to 12mm. It can be used in all weather conditions and is suitable for rough and porous surfaces. It has good low temperature resistance for freezers and cold applications. This product is toluene free.

Uses

Bond It **SAVES NAILS** is ideal for fixing a wide variety of materials to all types of walls and suitable for insulating PU foams. It can also be used to fix skirting boards, door surrounds and frames, window sills, all types of cladding, wall battens, decorative wall boards, metal carpet edges, automotive trims and much more. It can be used for interior and exterior applications.

It is ideal for use on: brick; some plastics*; timber; marble; stone; brick veneer; concrete; metal and ceramics.

** Solvent attack can occur with some plastics so test suitability before use.*

Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion.

Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Apply a 6mm bead (or thicker to suit gap) in a zig zag along one length of the item to be fixed. Press into place and apply an even pressure on the entire surface, leave to cure for 48 hours. Temporary support or fixings are recommended on very heavy items whilst curing.

Bracing or additional mechanical fastening is recommended for ceiling or heavy wall panels while the adhesive develops full strength. When bonding foam to ceiling additional mechanical fastenings are to be used.

Excessive material can be removed using Bond It **WHITE SPIRIT** or cellulose thinners. Clean tools immediately after use.



Limitations

- Not suitable for areas subject to frequent water immersion.
- Not recommended for use on asphalt, bitumen or polystyrene.
- Not to be used as a mirror adhesive.
- Dusty or porous surfaces should be primed with a primer prior to application - consult our technical department for details.

Container Size

EU3 polyamide cartridge.

Shelf Life

12 months from date of manufacture, when stored in unopened cartridges.

Storage Conditions

Store in cool, dry conditions. Keep containers in a well ventilated area. Must be stored in accordance with flammable liquid storage regulations.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

In the event of spillage remove all sources of ignition, ventilate the area, remove people from confined areas. Material should be mopped up immediately with an inert absorbent material such as sand or sawdust and scooped up with non-sparking tools.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Highly flammable
Full Cure Time	48 hours depending on bead thickness and temperature
Flashpoint	Less than 5°C
Shear Strength	3.5N/mm ²
Density	1.5
Yield	Approx 10 linear metres
UFI	6500-W02D-E00N-QVHG



Product Details:

Colour:	Beige/ Buff
Code:	BDSN2
Size:	EU3
Barcode:	5060021361615



Part of the Bond It Glues & Adhesives Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 16/02/21
 Supersedes: V3 03/09/14