



Never compromise on quality!



SAVES NAILS ON A ROLL

Strong Double Sided Adhesive Tape



DECORATORS RANGE

Description:

For interior and exterior use. Ideal for mounting items on ceramic tiles, painted surfaces, glass, metal and plastics.

Uses

High strength, water resistant, double sided adhesive tape for internal and external fixing. Good for bonding badges, name tags, protective mouldings, interior mirrors and other lightweight items. Excellent adhesion to metals, glass, ceramic tiles, painted surfaces and many plastics.

Application

1. Clean the surface thoroughly and allow to dry.
2. Cut to the required length and apply, using firm pressure, to the item to be stuck.
3. Once in position remove protective red liner and bond to second surface, applying firm pressure to ensure bonded securely.

Load Capacity

40Kg per m of tape.

Limitations

Do not touch the adhesive.

Do not apply at temperatures below +10°C.

Not recommended for use on wallpaper, stone, wood or dusty surfaces.

Size

19mm x 1.5M roll.

Shelf Life

18 months from date of manufacture when stored in original, unopened packaging.

Storage Conditions

Store in a cool, dry conditions at a temperature of 22°C and 50%RH. Keep away from direct sunlight and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Carrier	Acrylic foam
Adhesive	Acrylic
Release Liner	Red PE/paper
Thickness	1.0 ± 0.1mm/ 0.039 ± 0.004 inches
180° Peel Adhesion ASTM D-3330	2700g per 25mm / 6 lbs per inch
Tensile Adhesion	7030g/cm ³ / 100lbs per inch ²
Dynamic Shear ASTM D-1002 (stainless steel room temperature 24 hrs)	4900 /cm ² / 70lbs per inch ²
Temperature Resistance	Short Term: -40 to + 150°C Long Term: -40 to + 90°C
UV Resistance	Good

Product Details:

Code:	BDSN2T
Size:	19mm x 1.5M
Colour:	Clear
Barcode:	5060021369918



Part of the Bond It Decorating Sundries Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 **Fax** +44 (0)1422 315310
Email: salesuk@bonditgroup.com **Website:** www.bonditgroup.com

bond it
V2 15/02/21
 Supersedes: V1 30/07/14