

SAVES NAILS ON A ROLL

Strong Double Sided Adhesive Tape

Technical Data Sheet



DECORATORS RANGE

Description:

Multi-purpose wipes for cleaning hands, tools and surfaces. Powerful anti-bacterial performance.

Features & Benefits:

- ◆ **Extra strong.**
- ◆ **Works on painted surfaces, glass, metal, plastic and ceramic.**
- ◆ **Load capacity 40Kg.**
- ◆ **UV resistant.**
- ◆ **Interior and exterior use.**

Uses

High strength, water resistant, double sided adhesive tape for internal and external fixing. Good for bonding badges, name tags, protective mouldings, interior mirrors and other lightweight items. Excellent adhesion to metals, glass, ceramic tiles, painted surfaces and many plastics.

Limitations

Do not touch the adhesive.
Do not apply at temperatures below +10°C.
Not recommended for use on wallpaper, stone, wood or dusty surfaces.

Application

1. Clean the surface thoroughly and allow to dry.
2. Cut to the required length and apply, using firm pressure, to the item to be stuck.
3. Once in position remove protective red liner and bond to second surface, applying firm pressure to ensure bonded securely.

Load Capacity

40Kg per m of tape.

Size

19mm x 1.5M roll.

Shelf Life

18 months from date of manufacture when stored in original, unopened packaging.

Storage Conditions

Store in a cool, dry conditions at a temperature of +22°C and 50%RH. Keep away from direct sunlight and protect from frost.



Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any packaging or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Carrier	Acrylic foam
Adhesive	Acrylic
Release Liner	Red PE/paper
Thickness	1.0 + 0.1mm/ 0.039 + 0.004 inches
180° Peel Adhesion ASTM D-3330	2700g per 25mm / 6 lbs per inch
Tensile Adhesion	7030g/cm ³ / 100lbs per inch ²
Dynamic Shear ASTM D-1002 (stainless steel room temperature 24 hrs)	4900 /cm ² / 70lbs per inch ²
Temperature Resistance	Short Term: -40 to +150°C Long Term: -40 to +90°C
UV Resistance	Good
Commodity Code	3919101990

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDSN2T	Clear	19mm x 1.5M	5060021364753	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2.

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

Version 2: Updated 15/02/21
Supercedes: V1 30/07/14

bond it