

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

Bond It Universal Render (Grey)

DOP - BDER25



EN 998-1:2010

One Coat Rendering Mortar for External Use (OC)

Attestation Level 4

Essential Characteristic	Performance
Water Absorption	NPD
Water Vapour Permeability	NPD
Durability: Adhesion after Weathering Cycles	$\geq 0.2 \text{ N/mm}^2$ (B)
Durability: Water Permeability after Weathering Cycles	NPD
Reaction to Fire	Class A1



Phil Radford
Technical Manager
Seal It Services Ltd T/As Bond It
Unit G16 River Bank Way,
Lowfields Business Park
Elland, West Yorkshire
HX5 9DN
United Kingdom

Issue 1: May 2015

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

Bond It Universal Render (Grey)

DOP - BDER25



EN 998-1:2010

One Coat Rendering Mortar for External Use (OC)

Attestation Level 4

Essential Characteristic	Performance
Water Absorption	NPD
Water Vapour Permeability	NPD
Durability: Adhesion after Weathering Cycles	$\geq 0.2 \text{ N/mm}^2$ (B)
Durability: Water Permeability after Weathering Cycles	NPD
Reaction to Fire	Class A1



Phil Radford
Technical Manager
Seal It Services Ltd T/As Bond It
Unit G16 River Bank Way,
Lowfields Business Park
Elland, West Yorkshire
HX5 9DN
United Kingdom

Issue 1: 20th October 2022