

## DECLARATION OF PERFORMANCE

### DOP – BDGIST T/ WH



- |   |  |
|---|--|
| <p>1 Identification Code:</p> <p>2. Batch Identification:</p> <p>3. Intended uses:</p><br><p>4. Manufacturer:</p><br><p>5. Authorised Representative:</p><br><p>6. System of assessment and Verification of constancy:</p><br><p>7. Notified Body:</p> <p>8. European Technical Assessment:</p> <p>9. Declared performance:</p> | <p><b>BDGIST:</b> Bond It The One Silicone<br/>By batch number – see print on packaging<br/><b>F EXT-INT</b> Façade Sealant for Exterior and Interior Use 25LM. <b>G 25LM</b> Glazing Sealant 25LM. <b>XS1</b> Sanitary Sealant. <b>PW EXT_INT</b> Sealant for exterior and interior Pedestrian Walkways <b>CC</b> suitable for cold climates<br/>Seal It Services t/a Bond It<br/>Unit G16 River Bank Way<br/>Lowfields Business Park<br/>Elland<br/>West Yorkshire, HX5 9DN<br/>Not applicable</p> <p>System 3</p> <p>0757</p> <p>Not Applicable</p> |
|---|--|

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2,3,4:2012 Conditioning method A Tested on Mortar M1 without primer, Glass without primer, Aluminium without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties at maintained extension	Pass	
Tensile Properties – secant modulus	<0.9MPa	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Adhesion/cohesion after exposure to heat, water and artificial light	Pass	
Microbiological Growth	XS1	
Elastic Recovery	>70%	
Tear Resistance	Pass	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

A handwritten signature in blue ink, appearing to read 'T. Bham', is written over the printed name.

Travis Bham  
Product Development Manager  
Elland

**Issue 1:** 16 Jan 2017