

DECLARATION OF PERFORMANCE**DOP - BDHA6**

- 1 Identification Code: **BDHA6**: Bond It HA6 RTV Silicone
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior & Interior Use. **G 25LM** Glazing Silicone.
4. Manufacturer: Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: NB01213
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012 Conditioning method A Tested on aluminium without primer, glass without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland

Issue 2: 29th Feb 2016

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com

DECLARATION OF PERFORMANCE**DOP - BDHA6**

- 1 Identification Code: **BDHA6**: Bond It HA6 RTV Silicone
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior & Interior Use. **G 25LM** Glazing Silicone.
4. Manufacturer: Seal It Services Ltd t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: NB01213
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012 Conditioning method A Tested on aluminium without primer, glass without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland

Issue 1: 20th October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com