


**DECLARATION OF PERFORMANCE****DOP – BDLEAD**

- 1 Identification Code: **BDLEAD: Bond It FLASH-MATE LEAD SEALANT**
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use  
**G** Glazing sealant
4. Manufacturer: Seal It Services t/a Bond It  
Unit G16 River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0757
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method B
Loss of Volume	≤30%	Mortar M1 with primer
Tensile properties at 23°C	≥25%	
Tensile properties at maintained extension	NF	EN 15651-2:2012
Adhesion/cohesion at variable temperatures	NF	Conditioning method B
Adhesion/cohesion at maintained extension after water immersion	NF	Glass without primer
Durability	NF	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Amy Oxley  
Regulatory & Technical Data Manager

## DECLARATION OF PERFORMANCE

### DOP – BDLEAD




- 1 Identification Code: **BDLEAD: Bond It FLASH-MATE LEAD SEALANT**
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use  
**G** Glazing sealant
4. Manufacturer: Seal It Services t/a Bond It  
Unit G16 River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 0757
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method B
Loss of Volume	≤30%	Mortar M1 with primer
Tensile properties at 23°C	≥25%	
Tensile properties at maintained extension	NF	EN 15651-2:2012
Adhesion/cohesion at variable temperatures	NF	Conditioning method B
Adhesion/cohesion at maintained extension after water immersion	NF	Glass without primer
Durability	NF	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Amy Oxley  
Regulatory & Technical Data Manager

**Issue 1:** 20/10/2022

*Seal It Services Ltd/ T/As Bond It: Tel: 01422 315300*  
*Web: [www.bonditgroup.com](http://www.bonditgroup.com)*