

DECLARATION OF PERFORMANCE
DOP – GRIPBOND PRO (BDMSP CL/WH/BL/GR/BR)




- 1 Identification Code: **BDMSP: Bond It GRIPBOND PRO Adhesive and Sealant**
2. Batch Identification: **By batch number – see print on packaging**
3. Intended uses: **F-INT Façade sealant for Internal use**
4. Manufacturer: **Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN**
5. Authorised Representative: **Not applicable**
6. System of assessment and Verification of constancy: **System 4**
7. Notified Body:
8. European Technical Assessment: **Not Applicable**
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012
Resistance to Flow	< 3mm	Conditioning method A
Loss of Volume	<45%	Tested on aluminium without primer
Tensile properties after water immersion	>25%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Amy Oxley, Regulatory and Technical Data Manager

Seal It Services Ltd T/A Bond It
Unit G16 River Bank Way, Lowfields Business Park
Elland, West Yorkshire. HX5 9DN. United Kingdom
Issue 3: 1st February 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com

DECLARATION OF PERFORMANCE
DOP – GRIPBOND PRO (BDMSP CL/WH/BL/GR/BR)



- 1 Identification Code: **BDMSP: Bond It GRIPBOND PRO Adhesive and Sealant**
2. Batch Identification: **By batch number – see print on packaging**
3. Intended uses: **F-INT Façade sealant for Internal use**
4. Manufacturer: **Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN**
5. Authorised Representative: **Not applicable**
6. System of assessment and Verification of constancy: **System 4**
7. Notified Body:
8. European Technical Assessment: **Not Applicable**
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012 Conditioning method A Tested on aluminium without primer
Resistance to Flow	< 3mm	
Loss of Volume	<45%	
Tensile properties after water immersion	>25%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

A Oxley

Amy Oxley, Regulatory and Technical Data Manager
Seal It Services Ltd T/A Bond It
Unit G16 River Bank Way, Lowfields Business Park
Elland, West Yorkshire.
HX5 9DN. United Kingdom

Issue 1: 30th October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 Web: www.bonditgroup.com