

DECLARATION OF PERFORMANCE

DOP - BDPU18 (WH/BL/GR/BG) PU600 (BL/GR/WH)




- | | |
|--|--|
| 1 Identification Code: | BDPU18/ BDPU600: Bond It PU18 Polyurethane Adhesive and Sealant |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT-CC 25HM Façade sealant for External & Internal use. PW-EXT-INT-CC 25HM Sealant for walkways for pedestrian walkways. |
| 4. Manufacturer: | Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 2538 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,4:2012 Conditioning method A Tested on mortar/glass (façade elements) Tested on mortar (pedestrian walkways)
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties after water immersion	No failure	
Tensile properties, secant modulus	>0.4	
Tensile properties, secant modulus (-20°C)	>0.6	
Tensile properties at maintained extension	No failure	

Tensile properties at maintained extension – Cold climate	No failure	
Adhesion/Cohesion at variable temperatures	No failure	
Tensile properties after immersion in salt water	No failure	
Tear Resistance	No failure	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Dean Morgan
Managing Director
Elland

Issue 3: 9/11/22



Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

DOP - BDPU18 (WH/BL/GR/BG) PU600 (BL/GR/WH)




- 1 Identification Code: **BDPU18/ BDPU600:** Bond It PU18 Polyurethane Adhesive and Sealant
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT-CC 25HM** Façade sealant for External & Internal use. **PW-EXT-INT-CC 25HM** Sealant for walkways for pedestrian walkways.
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: 2538
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,4:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤10%	Tested on mortar/glass (façade elements)
Tensile properties after water immersion	No failure	Tested on mortar (pedestrian walkways)
Tensile properties, secant modulus	>0.4	
Tensile properties, secant modulus (-20°C)	>0.6	

Tensile properties at maintained extension	No failure	
Tensile properties at maintained extension – Cold climate	No failure	
Adhesion/Cohesion at variable temperatures	No failure	
Tensile properties after immersion in salt water	No failure	
Tear Resistance	No failure	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Dean Morgan
Managing Director
Elland

Issue 3: 9/11/22