

DECLARATION OF PERFORMANCE
DOP – BDSANX (WH/CL/GR)



- | | |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| 1 Identification Code: | BDSANX: Bond It Xtreme Always Silicone |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F INT Façade Sealant for Interior Use. XS1 Sanitary Sealant. |
| 4. Manufacturer: | Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire, HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,3:2012 Conditioning method B Tested on Mortar M1 without primer, Aluminium without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties– Secant modulus	< 0.4 MPa	
Tensile properties at maintained extension	Pass	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Microbiological Growth	XS1	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland

Issue 2: 10 Jan 2017

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com

DECLARATION OF PERFORMANCE

DOP – BDSANX (WH/CL/GR)



- | | |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| 1 Identification Code: | BDSANX: Bond It Xtreme Always Silicone |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F INT Façade Sealant for Interior Use. XS1 Sanitary Sealant. |
| 4. Manufacturer: | Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire, HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,3:2012 Conditioning method B Tested on Mortar M1 without primer, Aluminium without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties– Secant modulus	< 0.4 MPa	
Tensile properties at maintained extension	Pass	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Microbiological Growth	XS1	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland

Issue 2: 10 Jan 2017

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com