

# PACKING TAPE

## High Tack Packaging Tape



### TIGRIS TAPE RANGE

#### Description:

*A high tack packaging tape with acrylic dispersion adhesive.*

#### Uses

For use with most types of packaging; paper, card, plastic, etc.

#### Application

1. Ensure surfaces are clean, free from dust and dry.
2. Remove outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

#### Colour

Available in brown.

#### Size

48mm x 66M rolls.

#### Storage Conditions

Store in cool, dry conditions.

#### Shelf Life

Maximum 5 years from date of manufacture.

#### Disposal of Containers

Do not leave unused product or discarded material on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.

#### Health & Safety

This product will cause no major hazard or problem to the users health.

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of

children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

*Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.*



## Specification Summary

Base Material	Biaxially orientated polypropylene film
Adhesive	Acrylic water dispersion
Thickness of Film	23 micron
Elongation	100%
Adhesion to Steel	> 185 g/cm
Rolling Back Tack	< 8.5cm
Shear Strength	> 100 minutes
Anchorage	< 15%
Core Diameter	76mm

### Product Details:

<b>Colour:</b>	Brown
<b>Code:</b>	BDBT48
<b>Size:</b>	48mm x 66M
<b>Barcode:</b>	N/A



Part of the Bond It Tape Range

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number:  
6152  
ISO 9001; ISO 14001;  
ISO 45001

**BOND IT**  
**Head Office:** Unit G16 River Bank Way, Lowfields Business Park,  
 Elland, West Yorkshire HX5 9DN.  
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
 Email: [salesuk@bonditgroup.com](mailto:salesuk@bonditgroup.com) Website: [www.bonditgroup.com](http://www.bonditgroup.com)



**V1 27/06/18**  
 Supersedes: V