



COVER-IT CARPET PROTECTOR

Self-Adhesive Protection Sheet For Carpets And Textile Surfaces

Technical Data Sheet

DECORATORS RANGE



Description:

A high performance, self-adhesive protection material for covering and protecting synthetic carpets and textiles against mess, dirt, spillages and staining, etc., whilst painting and decorating, plastering, tiling and general building and maintenance projects.

Features & Benefits:

- ◆ **Self-adhesive.**
- ◆ **Low tack, temporary fix - can be removed easily.**
- ◆ **Tear resistant.**
- ◆ **Fully waterproof.**
- ◆ **Safer to use than loose dust sheets and coverings.**
- ◆ **Heavy duty.**
- ◆ **For interior use.**

Uses

For use on synthetic carpets and other textile coverings. Easy application, simply unwind, roll and COVER-IT.

Limitations

- DO NOT use on long pile/ wool carpets.
- In rare circumstances, COVER-IT can leave sticky residues on certain surfaces so it is recommended test areas be carried out prior to application.
- Replace COVER-IT after 4 weeks. Any unexpected residue can be easily removed by hand or with Bond It MULTI-WIPES - dependant on surface, check the compatibility of any fabric dyes with the wipes in an inconspicuous area first.
- Check textiles carefully before application - any textiles with lightly held fibres or fringes may detach when the film is removed the user should inspect textiles for any potential weak points before application.
- Do not use underfloor heating whilst COVER-IT is in position or 24 hours prior to application.
- In heavily trafficked areas or if exposed to excessive light or heat, replace at least once a week, checking for any residues left on the carpet.
- Carpets newly laid using adhesive will require 72 hours for the vapours to dissipate before application of COVER-IT film.
- COVER-IT will not adhere to damp or wet textiles. Recently cleaned carpets and uncured concrete floors: after film application moisture vapour is prevented from escaping and may cause discolouration of carpet fibres.
- Disposable - singular use only.
- Not suitable for hard surfaces, rugs or loose carpet tiles.
- Slippery when wet.



Application

Perform a compatibility test on an inconspicuous area prior to full application. Ensure the surface is free from dust, moisture and grease before application.

Place the roll onto the floor with the open end facing away from the direction it is to be applied. Unpeel approx 300mm (12") of the protective cover and press it to the surface firmly by hand. Push the roll away from you making sure it follows a straight line, smoothing it out as it unwinds to eliminate air bubbles or creases. Ensure film is safely and securely positioned before commencing work.

Removal

Easy and simple - the low tack adhesive will allow for easy removal. Lift each edge in turn and pull back towards the middle to keep any contaminants central on the roll ensuring any spills are covered and cannot escape before lifting the whole sheet. Take care when removing from textiles with loosely held fibres or fringes.

Size

Available in rolls of 600mm widths by 25 and 50 metre lengths.

Colour

Clear plastic film.

Shelf Life

Minimum 12 months from date of manufacture.

Storage Conditions

Store in cool dry conditions between +5 and +25°C. Safe in normal use however as a precaution keep polythene outer packaging away from children. Keep away from direct sunlight and protect from frost

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Dispose of in accordance with local regulations – sheet is polythene. Container is cardboard which can be widely recycled locally.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Clear polyolefin film
Adhesive	Pressure sensitive acrylic
Thickness	<50 microns
Application Temperature Limit	Between +15°C to +25°C
Commodity Code	3921909000

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDCICP25	Clear	600mm x 25M	5060021369499	-
BDCICP50	Clear	600mm x 50M	5060021369857	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 4: Updated 09/09/24
Supercedes: V3 20/03/17



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

bond it

An **ASTRAL** Limited Company