



UK  
CA



# MEGA STICK PU FOAM ADHESIVE

## Fast Curing PU Adhesive Foam

### Technical Data Sheet



## PU FOAM & ADHESIVE RANGE

### Description:

*A low expansion PU foam adhesive which reacts with atmospheric moisture to set.*

### Features & Benefits:

- ◆ *Saves time and labour costs.*
- ◆ *Can be plastered in 1 hour.*
- ◆ *No heavy bags to carry.*
- ◆ *One can will fix approximately 5 standard boards.*
- ◆ *Suitable for use on solid walls, metal and timber studding.*
- ◆ *No nails or screws. No filling over or popping out.*
- ◆ *Easy application - no mixing or mess.*

### Uses

Bond It MEGA STICK is a fast curing adhesive foam that has been specially developed for the rapid installation of plasterboard, insulation boards, floorboards and roof decking. Supplied in an aerosol can, application is by universal foam gun.

Ideal for the installation of insulation boards and plaster boards to solid walls, metal and timber stud walls and battens. For fixing roof decking and floorboards to beams. And in place of backing rods in expansion joints and around window and door frames. It adheres to most common building materials:- extruded and expanded polystyrene; mineral wool; polyisocyanurate and polyurethane foam; plaster, gypsum boards; concrete, brick, stone; wood; metals; bituminous membranes.

### Properties

The foam can be used at temperatures from +5°C to +35°C, the optimal processing temperatures being from +18°C to +25°C. Full foam setting time is 12 hours. It is thermally stable between -40°C and +100°C. It is durable and permanent except when exposed to UV-rays.

### Preparation

Protect all surfaces from drips of foam by using paper or plastic sheets. As the foam needs moisture to cure to achieve best results mist the substrate with water prior to application.

### Application

**As from 24 August 2023 adequate training is required before industrial or professional use.**

The instructions for the can must strictly be observed. Use gloves

and eye protection and avoid skin contact.

If necessary, gently warm chilled cans in lukewarm water before use. Do not heat cans above +50°C as there is risk of bursting. Shake the can for at least 30 seconds then fix the foam gun to the can. The can will operate in any position.

If fixing boards, apply beads to the back of the board wait approximately 2 minutes then press the board into place. If using insulation board apply 3 beads approximately 25mm wide to the board. If using plasterboard apply approximately 400mm apart. Use mechanical fixings if working overhead. Apply the boards in rows, starting from the bottom of the wall, and going up to the top to avoid sliding. Apply to the substrate within 5 minutes of applying adhesive (depending on ambient conditions) and press firmly across the whole face of the board, starting at the top. Apply subsequent boards ensuring edges are firmly butted up at this stage.

Hold board in place for approx 1 minute until adhesive is cured enough to hold the board on its own. Plastering can commence after 1 hour!

If using a gun and you have not used all the can, clean the gun using Bond It GUN FOAM CLEANER, screw in proportioning screw which will ensure the foam will be usable for up to approximately 4 weeks.

### Limitations

Cured foam is sensitive to UV light and direct sunlight and therefore should be covered with suitable opaque sealant, filler, paint or other material. Not recommended for use on polyethylene, silicone, oil and grease.

### Cleaning

Excess foam can be removed whilst still wet using Bond It FOAM CLEANER or MULTI-WIPES.

Cured foam can only be removed mechanically.

### Coverage

Depending upon substrate condition and porosity 5-10 linear metres with a 25mm bead per cartridge.

### Size

Minimum 750ml aerosol canister.



## Shelf Life

Minimum 12 months from date of manufacture when stored in original, unopened canister. Once opened shelf life is reduced to 1 month.

## Storage Conditions

Store and transport upright, in cool, dry conditions between +5°C and +25°C. (Do not store in hot cars or vans as can may explode. Maximum storage temperature is +30°C. Protect from frost.

## Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a

central disposal point in accordance with local regulations.

## Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control.**

## Specification Summary

Surface Dry	10-12 minutes
Full Cure	1 hour
Adhesion To Expanded Polystyrene (N/mm <sup>2</sup> )	0.033
Adhesion To Extruded Polystyrene (N/mm <sup>2</sup> )	0.039
Density	20-25Kg/m <sup>3</sup>
Volume Shrinkage %	None
Post Expansion	% 5
Flashpoint Of Cured Foam	ca. 310°C
Temperature Resistance Of Cured Foam	Long term: -40 to +100°C
Commodity Code	3214900000



## Product / Order Details

Code	Colour	Size	Barcode	UFI
BDEFMS	Beige	750ml	506002136817	OK80-X0Q6-G00E-6WN9

**Note:** The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



## Part of the Bond It PU Foams & Adhesives Range

**Head Office:** Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

**Telephone:** +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

**EU Office:** SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2.

**Website:** www.bonditgroup.com



Certificate Number 6152  
ISO 9001  
ISO 14001  
ISO 45001

**Version 7: 08/04/24**  
Mercedes V6 13/10/22

