

STABILIZING SOLUTION

Water-Based Bonding and Priming Agent

Technical Data Sheet



BUILDERS COMPLETE RANGE

Description:

A white, ready to use, water-based treatment for bonding and priming surfaces prior to painting and decorating.

Features & Benefits:

- ◆ Solvent-free.
- ◆ Quick drying.
- ◆ Stabilizes poor surfaces.
- ◆ Seals and binds chalky or weathered areas.
- ◆ Can be applied to damp surfaces.
- ◆ Provides a sound base for decorating.
- ◆ For interior and exterior use.

Uses

For use as a pre-treatment for surfaces which are old, weathered, chalky or porous. Suitable for use on most substrates including concrete, cement, plaster, plasterboard, renders, pebbledash and MDF, etc.

Limitations

Do not apply STABILIZING SOLUTION when the temperature is below +5°C or when rain or frost is imminent. However, this product can be applied to damp substrates.

Preparation

Ensure all surfaces are clean and free from any contaminants including loose and flaking material. Remove any mould or algae with MOULD-STOP or PATIO BLASTER prior to application.



Application

Do not dilute. Stir well and apply by brush, roller or airless spray. A second coat may be required on porous or powdery surfaces but allow 12 hours drying time between application of coats.

Cleaning Of Tools

Rinse equipment after use with plenty of clean water.

Size

5L plastic bottle.

Coverage

6m² per litre, depending on porosity of substrate.

Colour

White liquid.



Shelf Life

24 months from date of manufacture when stored in unopened bottles.

Storage Conditions

Store in cool, dry conditions in original sealed container between +5 and +30°C. Protect from frost, high temperatures and direct sunlight.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any bottles or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	White liquid
Flammability	Non-flammable
pH	approximately 7-9
Solubility in Water	Soluble
Commodity Code	3209900000

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDH130	White	5L	5060021364777	-



Part of the Bond It Builders Complete Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 4: Updated 23/07/24
 Supercedes: V3 20/05/20



Certificate Number 6152
 ISO 9001
 ISO 14001
 ISO 45001

bond it

An **ASTRAL** Limited Company