



OIL STAIN REMOVER

Grease and Oil Stain Remover for Porous Surfaces

Technical Data Sheet



DRIVE ALIVE RANGE

Description:

An oil ingesting solution for removing unsightly oil and grease stains from porous surfaces such as tarmac and concrete.

Features & Benefits:

- ♦ *Easy to use - simply pour on stain, allow to dry and brush away.*
- ♦ *VOC free formulation.*
- ♦ *Bio-degradable.*

Uses

Excellent for oil and grease lifting from porous surfaces, such as pavements, slabs, drives, pathways and patios. Great for oil leaks from cars or grease spots from barbecues.

Limitations

Do not apply to wet or damp surfaces. Do not use if rain is imminent (protect from rain until dry). Do not use at temperatures below +5°C or above +30°C.

Preparation

Brush away any loose dirt and debris prior to application. Ensure the area to be treated is thoroughly dry.

Application

Shake well before use. Pour DRIVE ALIVE OIL STAIN REMOVER on to the oil or grease stain, ensuring the stain is completely covered. Simply leave until totally dry (minimum 3-4 hours). Cold or humid conditions will slow drying times. We would recommend leaving for 24 hours to ensure product has had sufficient time to absorb material effectively. Once dried, the area should be swept with a stiff broom to remove the dried product. Hose down the treated area to ensure all powder residue is completely removed.

For oil spills covering a larger area, OIL STAIN REMOVER can be diluted 1:1 with water. depending on the size of the area, a brush may be required to spread product. A second application may also be necessary.

If white residue remains after use, apply hot soapy water and scrub with a stiff brush until no longer visible.

Size

1L plastic bottles.

Coverage

1m² per 1L.



Colour

White creamy liquid.

Shelf Life

12 months from date of manufacture when stored in original sealed containers.

Storage Conditions

Store in cool, dry conditions in a sealed container. Store between +5°C and +25°C. Protect from frost and keep out of direct sunlight.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Physical Properties	White/opaque liquid
Flammability	Non flammable
Solubility in Water	Soluble
Density	1.05g/cm ³
Application Temperature Range	+5°C to +30°C
Drying Time	3-4 hours in warm, sunny conditions
Commodity Code	3402909000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BDOSR1	White	1L	5060021367297	ST70-X0GQ-P00Q-K8D7



Part of the Bond It Drive Alive Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 3: Updated 29/08/24
 Supercedes: V2 12/02/21



Certificate Number 6152
 ISO 9001
 ISO 14001
 ISO 45001

bond it

An **ASTRAL** Limited Company