



LIGHTWEIGHT SCRIM TAPE

Lightweight Drywall Joint Tape

Technical Data Sheet



TIGRIS TAPE RANGE

Description:

A trade grade, self-adhesive, fibreglass mesh tape which gives increased strength and extra reinforcement when joining plasterboard.


Features & Benefits:

- ◆ Self-adhesive and repositionable.
- ◆ Joins dry wall, plaster walls & ceilings.
- ◆ Repairs cracks & patches holes.
- ◆ Quick & easy to apply.
- ◆ Flexible, will not bubble/blister.
- ◆ Alkaline resistant - will not rot.

Uses

For joint finishing, crack and hole repair. For drywall and plaster walls and ceilings.

Application



1. Ensure surfaces are clean, free from dust and dry.
2. Remove outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

Size

2" (48mm) tape x 90m rolls.

Colour

White.

Shelf Life

24 months from date of manufacture.

Storage Conditions

Store in original, unopened packs in cool, dry conditions, out of direct sunlight between +5 and +25°C.



Disposal Of Containers

Do not leave unused product or discarded materials on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.

Health & Safety

This product will cause no major hazard or problem to the users health. Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Backing	100% glass fibre
Adhesive	Acrylic latex
Total Weight	approx 65gsm
Thickness	0.2 mm
Commodity Code	7019650019

Weight (g/m ²)	Fiberglass Yarn Tex		Tensile Strength (N/50mm)		Fabric Count (meshes/inch)			Latex (%)
	WARP	WEFT	WARP	WEFT	WARP	WEFT	TYPE	
65±5g/m ²	66	80	≥400	≥500	8±0.5	8±0.5	Leno weave	≥26

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDSCRIM	White	2" (48mm) x 90m	5056437400031	-

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Part of the Bond It Tape Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com



Certificate Number 6152
 ISO 9001
 ISO 14001
 ISO 45001

Version 1: 1/10/21
 Supersedes: V



An **ASTRAL** Limited Company