

SQUEEZE IT DOOR & WINDOW SEALANT

General Purpose Water Based Sealant

Technical Data Sheet



SQUEEZE IT SEALANT & ADHESIVE RANGE

CLASS
EN15651-1,1; F EXT-INT

Description:

A high quality, water resistant acrylic frame sealant with good adhesion to most building materials. Conforms to BS EN 15651-1:2012.

Features & Benefits:

- ◆ Excellent adhesion.
- ◆ Over paintable.
- ◆ Outstanding durability.
- ◆ Permanently flexible.
- ◆ For interior and exterior use.
- ◆ Good weathering properties.
- ◆ Non-shrinking.

Uses

Bond It SQUEEZE IT DOOR & WINDOW SEALANT is an easy to clean, flexible, water resistant joint filler which can be readily overpainted. It is suitable for sealing around door and window frames and soffit boards. It can also be used for filling cracks and joints with low movement.

It is ideal for use on: wood, concrete, brick, natural stone, artificial stone and most common building materials.

Limitations

This product is not a silicone sealant! Not suitable when:

- applied externally during rainy weather.
- applied at temperatures below +5°C.
- used in joints constantly immersed in water.
- used in contact with bituminous products.
- used in areas of high abrasion, e.g. floor joints.
- used with plastic baths - use a sealant with greater flexibility.

Preparation

All surfaces must be clean, dry, sound and free from dust, oil or any other contaminants that may hinder adhesion. If necessary, in addition to mechanical means, cleaning with a solvent such as acetone is recommended for degreasing.

Priming

SQUEEZE IT DOOR & WINDOW SEALANT does not require a primer on most common construction surfaces. However, in some cases it may be necessary to prime concrete or other surfaces for optimum adhesion. To determine whether a primer is required a sample should be tested.

Contact Bond It Technical Service Department for recommendations.

Application

Remove the cap and carefully cut the nozzle at an angle of 45° to an opening slightly larger than the gap to be sealed. Where there is a deep gap between the bath and the wall fill with foam strips to provide a backing for the sealant. Squeeze tube to extrude the sealant. Smooth down within 20 minutes using a slightly wetted spatula or SEALANT APPLICATOR TOOL wetted with soapy water. Remove excess product with a damp cloth. Do not saturate the surface with water, as this will delay curing the process. Ensure adequate ventilation to ensure drying, especially in cold damp conditions. Tools should be cleaned using water.



Note: Protect from water for 24 hours after application or until a tough skin has developed. Do not subject to pressurised water.

Maintenance

Resistant to all common household cleaning chemicals. In showers and bathrooms best results are obtained with a weekly clean to prevent organic build up.

Stains can be removed with commercial bleach.

Coverage

Depending upon substrate condition and porosity approximately 5 linear metres with a 6mm bead per tube.

Colour

Available in white only.

Size

EU2 plastic squeeze tube.

Shelf Life

Minimum 24 months from date of manufacture when stored in original unopened cartridges.

Storage Conditions

Store in cool, dry conditions at a temperature between +5°C and +25°C. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate Safety Data Sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Tooling Time	Tool within 5 minutes
Skin Time @20°C	After 20 minutes
Full Cure Time	24 hours depending on bead thickness and temperature
Application Temperature	+5°C to +30°C
Waiting Time Before Painting	1 hour for emulsion paints 24 hours for solvent based paints
Sag	None
Movement Accommodation	12.5%
UV and Weather Resistance	Good
Water Resistance	Good
Polluted Environments	Good
Density	1.7 g/cm ³

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BDSQFM	White	150ml	5060021366573	-

UK CA	CE
22	14
BOND IT G16 River Bank Way, Elland. HX5 9DN. UK	
EN15651-1,3:2012 F EXT-INT Facade sealant for interior use.	
Reaction to fire	E
Release of chemicals	None
Resistance to flow	≤ 3mm
Loss of volume	NPD
Tensile properties after water immersion	NPD
Durability	Pass



Part of the Bond It Silicone & Sealants Range

Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2.

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

Version 3: 24/11/23
Supersedes V2 11/02/21

bond it