

TARMAC RESTORER

Sealer For Protecting Tarmac Paths & Driveways



DRIVE ALIVE RANGE

Description:

A ready-to-use, black water based coating for tarmac drives and pathways.

Benefits:

- ◆ Restores tarmac colour.
- ◆ Helps protect from water damage.
- ◆ Ready to use.
- ◆ Reduces dirt/grime build-up
- ◆ Inhibits organic growth.
- ◆ Solvent-free.

Uses

Designed to restore colour, reduce water penetration, and protect from dirt/grime build-up.

Preparation

For best results use Bond It Mould Stop or Patio Blaster prior to application (ensure the residue is thoroughly washed off and left to dry for 48 hours prior to application.) Ensure the surface to be treated is free from oil, grease, dust and any other loose material that may hinder adhesion. It is recommended that a test be carried out on a small inconspicuous area to ensure the required effect is achieved.



Application

DRIVE ALIVE TARMAC RESTORER is ready to use, and does not require diluting. Stir thoroughly before using and ensure the surface is completely dry prior to application. Apply using a brush, roller or squeegee, ensuring that no pooling or ponding occurs. Two coats are recommended, allow a minimum of 4 hours between coats. Cold or humid conditions will slow drying times.

Limitations

Do not apply to wet or damp surfaces or in conditions of high humidity. Surfaces should be allowed to dry completely for 48 hours prior to application. Do not use if rain is imminent (protect from rain until dry). Do not apply to non-porous surfaces. Keep children and animals away and do not traffic until fully cured. Do not allow any run off to contaminate drains, waterways or plants. Do not use in temperatures below +5°C and above +30°C. **TARMAC RESTORER** is not recommended for use on permeable tarmac. As there may be differences in the colour between different production batches, always check that the batch numbers are the same when using multiple tubs.

Container Size

4L rectangular plastic tub.

Colour

Black liquid.

Coverage

Approximately 16-24m² per 4 litres, depending on surface porosity.

Shelf Life

24 months from date of manufacture when stored in unopened tubs.

Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Physical Properties	Blue/black liquid - dries black, non-flammable, water miscible
Application	Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	+5°C to +30°C
Drying Time	4 hours in warm, sunny conditions
Coverage Rate	16-24m ² per 4 litre container
Cleaning	Rinse then wash brushes and rollers in warm, soapy water
Shelf Life	2 years

Always check batch numbers match when using multiple tubs for one area as shades can vary.

Product Details:

Code:	BDTR4
Colour:	Black
Size:	4L
Barcode:	5060021368294



Part of the Bond It Drive Alive Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 03/06/19
 Supercedes: V3 11/06/12