

POWER-PROOF

Concentrated Water Resistant Plasticiser For Mortar and Render

Technical Data Sheet



BUILDERS COMPLETE RANGE

CLASS
EN934-3 T2

10
Times
Stronger Concentrate

Description:

A premium grade, concentrated integral water resistant plasticiser designed to improve resistance to water penetration both internally and externally whilst giving all the benefits of a mortar plasticiser. Conforms to EN934-3:2009 + A1 (2012), Class 2.

Features & Benefits:

- ◆ Improves the plasticity of the mix making it easier to use.
- ◆ Improves water resistance.
- ◆ Retards suction in multi-layer renders.
- ◆ Reacts with free lime in the mortar to form hydrophobic crystals which block the pores, thereby improving the water resistance of the mix.
- ◆ Simply add to gauging water.

Uses

To help mortars and renders resist external and/or internal water pressures. Suitable for use on renderings, retaining walls, tanks swimming pools, roof screeds, reservoirs, basement walls and all applications where water penetration is a problem.

Limitations

This is not a vapour-proofing product, therefore, a separate vapour-proof membrane is required for vapour-proof applications. Do not overmix the mortar/concrete, to prevent excessive air entrainment and subsequent loss of strength. Do not use at temperatures below +2°C or when temperature is expected to drop below 0°C within 24 hours.

Application

Shake well before use. This product is supplied in a carefully measured dosage bottle, simply squeeze the bottle to administer the correct amount of liquid into the delivery nozzle.

Add to gauging water in the ratio of 25-50ml Bond It POWER-PROOF to each 25Kg bag of cement and reduce the total volume of gauging water to achieve the desired consistency. Use the appropriate sand/cement ratio for dense high quality mortar. Ensure the mortar is firmly compacted and do not over mix the mortar. In multi-coat applications use the lowest dosage for under-coats and the highest in the final coat.

Size

1L plastic dosing bottle.

Coverage

25-50ml POWER-PROOF for every 25Kgs of cement.

Colour

Pink liquid.

Shelf Life

24 months from date of manufacture when stored in unopened bottles.

Storage Conditions

Store in cool, dry conditions in a sealed container between +5 and 30°C and protect from frost, high temperatures and sunlight.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any bottles or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.



Specification Summary

Appearance	Pink liquid
Flammability	Non-flammable
Boiling Point	100°C
Composition	Sodium lauryl ether sulphate mixture
Solubility in water	Soluble
pH	8.5
Application Temperature	+2°C to +30°C
Commodity Code	3824400000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
POWP1	Pink	1L	5060021364494	5220-1084-500J-9DAW

**UK
CA**

22

CE

13

BOND IT

H4 Premier Way, Elland. HX5 9HF. UK

EN934-3:2009 + A1:2012

Air entraining plasticiser for masonry mortar EN934-3 T2.

**DoP: POWP1
NB: 0120**

**DoP: POWP1
NB: 1029**

Maximum chloride ion content <0.1% by mass

Maximum alkali content <1.0% by mass

Corrosive behaviour Contains components only from EN934-1:2008 Annex A.1



Part of the Bond It Builders Complete Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

Version 6: Updated 11/06/24
Supercedes: V5 14/10/22

bond it

An **ASTRAL** Limited Company